

Engineering Data



7529

2 WIRE ULTRA THIN VIDEO MONITOR

The Elvox® 7529 monitors are designed to meet any requirement for Videointercom security. Unique capacitive touchscreen controls are programmable for use as door release, ring tone mute, camera activation, station to station calling and more. Ringtone selection and level control is provided. The 7529 has a special mirror gloss finish. An apartment doorbell input is provided and different ringtones can be selected for an intercom call and a doorbell call. The ultra low profile design is only 1.75" (45mm) including the handset. Separate input and output terminals and dip switch termination are provided for ease of installation.

General Information	Specifications
-Ultra Low Profile Design	System: 2 Wire Video
-3.5" LCD Hi Resolution	Controls: Capacitive door release, Self activation, Auxilliary Function, 4 extra programmable capacitive controls. Ringtone selection and level
-Twisted Pair Operation	
-Private Conversation	
-Tone Ring Signal	Handset: Duplex Handset with electret Mic and heavy duty coiled cord
-Duplex Voice Operation	
-Easy Surface Installation	Construction: Molded High Impact Plastic with mirror gloss finish White or black (7529/04)
-Capacitive Touchscreen Controls	Terminations: Screw Terminal
-Unique mirror gloss finish	Dimensions: 6.25" W., 7" H., 1.75" D.
-Doorbell input with distinct tone	Net Weight: 1 lb (.5 Kg)
-Easy to Install and Program	

2 Wire Low Profile Video Monitor
7529

Architects and Engineers Specification

The Elvox® 7529 monitors shall be designed to meet any requirement for Videointercom security. Unique capacitive touchscreen controls are programmable for use as door release, ring tone mute, camera activation, station to station calling and more shall be provided. Ringtone selection and level control shall be provided. The 7529 shall have a special mirror gloss finish. An apartment doorbell input shall be provided and different ringtones can be selected for an intercom call and a doorbell call. The ultra low profile design shall be only 1.75" (45mm) including the handset. Separate input and output terminals and dip switch termination are provided for ease of installation. The model 7529 (7529/04) is specified.

7529 Series

Rev 1.0